Aluminium profiles for it all.

HiluX LightSolutions

Eight profiles for recessed, corner, surface and waterproof outdoor mounting. Fits every HiluX LED strip and the most common Hue strips.



MODEL L recessed	MODEL L	MODEL M	MODEL G	MODEL S	MODEL C	MODEL U	MODEL W

Profile	10 mm Hue Essential	10.2 mm HiluX	14 mm Hue Solo	14.5 mm Hue Flux / V4	15 mm Hue Gradient	17 mm Hue OmniGlow	Colours
S	●	●	●	●			● ○ ●
C	●	●	●	●	●		● ○ ●
G	●	●	●	●			● ○ ●
M	●	●	●	●			● ○ ●
L	●	●	●	●		●	● ○ ●
L Recessed	●	●	●	●	●	●	● ○ ●
U	●	●	●	●			● ○ ●
W	●	●	●	●	●	●	● ○ ●

All profiles available in: ● Black ○ White ● Alu ● = Compatible with this strip width

THE WHOLE SYSTEM

One family.
One light quality.

Warm, uniform light across every HiluX LED strip — whether you choose 24 V or 230 V. Matching profiles, strips and accessories from the same family, so you can mix freely without seeing a difference.

CONTACT

We answer fast.

Danish support from HiluX experts.

LightSolutions

PHONE +45 53 71 20 12

EMAIL kontakt@lightsolutions.dk

WEB lightsolutions.dk

HiluX LightSolutions

LED STRIPS
2026

LED strips without compromise.

From ultra-fine COB to powerful 230V strips — HiluX LED strips deliver the same warm, uniform light throughout the home.



HIGH COLOUR RENDERING

DIMMABLE

24V OR 230V

3-YEAR WARRANTY



HiluX Highpower SMD

Item no. 97-019 · EAN 5714255011012

230 V · UP TO 50 M

Powerful 230V strip — runs straight off mains power with no driver. Perfect for long runs.

CRI / LUMEN	98 · 1200 lm/m
VOLTAGE	230 V AC · no driver
POWER	15 W/m · 2800 K
LENGTH	Up to 50 m
IP	IP67 · indoor & outdoor



HiluX Highpower COB

Item no. 97-007 · EAN 5714255009958

230 V · NO VISIBLE LEDS

COB technology — no visible LEDs, just an even line of warm light. Powerful and straight off 230 V.

CRI / LUMEN	95 · 845 lm/m
VOLTAGE	230 V AC
POWER	13 W/m · 3000 K
LENGTH	Up to 50 m
IP	IP67 · indoor & outdoor



HiluX RGBW

Item no. 97-008 / 97-009 · EAN 5714255009965 / 5714255010022

24 V · COLOUR + WARM WHITE

Red, green, blue and warm white in one strip. Full colour control plus a dependable white work light.

CRI / LUMEN	90 · 620 lm/m
VOLTAGE	24 V DC
COLOURS	R · G · B + 2700/3000 K
LENGTH	5 m
IP	IP20 / IP65 · indoor & outdoor



HiluX Longline

Item no. 97-001 / 97-002 · EAN 5714255009897 / 5714255009903

24 V · UP TO 20 M

Designed for long runs. Goes up to 20 m with no voltage drop — cable at both ends for flexible installation.

CRI / LUMEN	95 · 550 lm/m
VOLTAGE	24 V DC
LEDS	COB — none visible
LENGTH	5 / 10 m · cable both ends
IP	IP65 with heat-shrink



HiluX Highlumen

Item no. 97-005 / 97-006 · EAN 5714255009934 / 5714255009941

24 V · HIGH BRIGHTNESS

When you need a lot of light out of a single strip. High lumen, even appearance, no visible LEDs.

CRI / LUMEN	95 · 1300 lm/m
VOLTAGE	24 V DC
POWER	16 W/m · 2700/3000 K
LENGTH	5 m · cable both ends
IP	IP65 with heat-shrink



HiluX Neon

Item no. 97-033-3000K · EAN 5714255012712

24 V · FLEXIBLE NEON PROFILE

5 × 4 mm silicone neon with a bend radius down to 30 mm. Solderless joints keep installation simple.

CRI / LUMEN	90+ · 290 lm/m
VOLTAGE	24 V DC
POWER	10 W/m · 3000 K
DIMENSION	5 × 4 mm · R ≥ 30 mm
LENGTH	5 m · solderless
IP	IP54 · indoor & outdoor